

- 1). Standby Power: 1 Wat per hour.
- 2). Export Certificate: CE, 3C, ISO9001:2008
- 3). Height moving Noise: less than 30DBA.
- 4). Maximum loading Weight: above 250kgs
- 5). Abrasion:1% after moving 30,000 times.
- 6). Height adjustable range: 620 - 1270 mm
- 7). 1 motor in each legs, synchronous pulse control
- 8). Moving speed: Moving up at 25mm/s, moving down at 30mm/s
- 9). Operation Temperature:-20 Degree Celsius to 50 Degree Celsius
- 10).Duty Cycle: No lifting limited time on the working of motor
- 11).Color available for tube leg: Drawing or other color, please inform us
- 12).Color Available for beams: White, Sandy White,Grey,Black,Sandy Black,Silvery
- 13).Height adjustable by electric according to your power: 110Volts to 230Volts
- 14).All the Shore of the leg is made with Aluminum alloy tube frames at 2.0mm Thick
- 15).Metal Beam is 3.0mmT Cold Rold steel with Anti-rust treatment,Guarantee for 5 years
- 16).Height adjustable at 4 pre-set digital control panel for memory height just by click!
- 17).Height Controlling systems could be in touching pad or Touch Panel,even wireless control system
- 18).Height adjustable frame with adjustable cup at bottom of the legs. wheels here is not considered
- 19). When the height moving in different size, Press P at the right side for 3s, it will reach the same H
- 21).Motors here could connect for around 4 pcs to tall at the same time





www.sheetmetal-fabrication.com www.houdry.com.cn



www.sheetmetal-fabrication.com www.houdry.com.cn