

- 1). Standby power: 1 watt per hour.
- 2). Export Certificate: CE, 3C, Iso9001: 2008
- 3). Height moving noise: less than 30dBA.
- 4). Maximum Loading Weight: Above 250kgs
- 5). Friction: 1% after running 30,000 times.
- 6). Height Adjustable Range: 620 - 1270mm
- 7). 1 motor in each foot, synchronous pulse control
- 8). Moving Speed: Moving at a speed of 25 mm / sec, moving at a speed of 30 mm / second
- 9). Operation temperature: -20 ° C to 50 ° C
- 10). Duit bicycle: Limited time to do motor work
- 11). Available colors for tube feet: Drawing or other colors, please inform us
- 12). Available for color beam: white, sandy white, gray, black, sandy black, silver
- 13). Adjustable adjustable by electric according to your power: 230Volts from 110Volts
- 14). All the edges of the foot are made on aluminum alloy tube frame with 2.0mm thick
- 15). Metal beam is 3.0 mm T cold rolled steel with anti-corrosion treatment, 5 years guarantee
- 16). High Editing for High Editing by Clicking on 4 Pre-set Digital Control Panel!
- 17). high controlling system can also be in touch pad or touch panel, wireless control system
- 18). Adjustable adjustable frame with adjustable cup at the bottom of the foot. Wheels are not considered here
- 19). When the height runs in different sizes, press P on the right for 3p, it will reach the same H
- 21). People here can connect up to 4 pcs at the same time





www.sheetmetal-fabrication.com www.houdry.com.cn



www.sheetmetal-fabrication.com www.houdry.com.cn